



Executive Bus

## EXECUTIVE BUS

### Features

- Available in BS-III & BS-IV versions
- Powerful engine-Higher pick up. Higher torque at lower RPM
- Gradeability & Fuel efficient
- Available in BS-III & BS-IV versions
- Powerful engine-Higher pick up. Higher torque at lower RPM

<b>ENGINE</b>	
Model	SLT3 EURO III Compliant
TYPE	4 Cylinder, In-Line direct Injection Water Cooled Turbo charged with inter cooler.
Displacement (cc)	3456
Max Power	100 PS (75 kw) @ 3000 rpm
<b>ELECTRICALS</b>	
Type	12 VOLTS
Battery	2 NOS. 12V, 70AH
<b>DRIVE TRAIN</b>	
Clutch	Dry single plate with diaphragm spring Hydraulically controlled
Transmission	5 Forward, 1 Reverse
<b>AXLES</b>	
Front Axle	Reverse Elliot "I" Beam Section
Rear Axle	Full floating Banze type
<b>STEERING</b>	
Type	Re-Circulating ball type, Power
<b>SUSPENSION</b>	
Front	Semi elliptical type multi leaf spring with hydraulic double acting telescopic shock absorbers
Rear	Semi elliptical type multi leaf spring with hydraulic double acting telescopic shock absorbers
Optional	Air Suspension



### Features

- Aero Dynamic Shape
- Roof Mounted A/C with individual Ducts
- Reading Lights
- HairRacks
- DVD Player with LCD Screen
- Driver Controlled Passenger Door
- Tinted Sealed Glasses
- Curtains

<b>BRAKES</b>	
Service Brakes	Hydraulic dual circuit with hydraulic servo assist
Parking Brake	Mechanical Expanding type at rear of transmission
Exhaust Brake	Provided
<b>WHEELS AND TYRES</b>	
Wheels	5 Stud Wheel Discs
No. of Tyres	5 (Including 1 Spare Tyre)
Size	7.50 X 16-14 - PR Cross
<b>FUEL TANK</b>	
Capacity	90 LTRS
<b>PERFORMANCE</b>	
	Dry single plate with diaphragm spring.
Max Speed	98 km / hr
<b>SEATS</b>	
No. of Seats	13+1
Type	Push Back, Reclining Comfortable Seats with padded Arm Rests and Foot Rest
<b>DIMENSIONS</b>	
Wheel Base	2615 MM
Ground Clearance	206 MM
Overall Length	5875 MM
Overall Width	2155 MM
Overall Height	3125 MM
<b>TRACK</b>	
Rear	1640 MM
Front	1640 MM