

S7 BUS

Features

- Driver Comfort
- Better driver cockpit
- Large wind shield. Better driving view
- Suitably located gear shift leaver for better comfort
- Time tested and proven engine

Model	S7 Bus BS - III	S7 Bus BS-IV
Engine & Displacement	SLT3 & Numeral , 3455 cc	SLT4 & Numeral , 3455 co
Туре	In line 4-Cylinder Direct Injection	In line 4-Cylinder Commar Rail Direct Injection
1	Diesel Turbo Charger with Intercoo	ler
Max.Engine Output	75 Kw @3000 rpm	75 Kw @2800 rpm
Max. Torque	270Nm@1750-2000 rpm	296Nm @ 1500 rpm
Clutch	Single plate Diaphragm Type , Dia. 260mm	
Gear Box	Synchromesh Manual 5-Forward and 1-Reverse	
Steering	Power Steering	
Brakes	Air Brake	
Suspension	Semi Ellipitical Type Multi Leaf Spring	
Variants	S7 Bus BS – III	
High head rest seats (2X2)	40+1	
Fuel Tank capacity (Its)	90	
Dimensions		
Wheelbase	5100	
Overall Length (mm)	9280	
Overall Width (mm)	2262	
Overall Height (mm)	2960	
Rear Overhang (mm)	3000	
Front Overhang (mm)	1180	
Wheels & Tyres	8.25 X 16 -16PR	
No. of tyres	6+1	
Max. Permissible GVW (kg)	8880	







Features

Driver Comfort

Better driver cockpit

Large wind shield. Better driving view

Suitably located gear shift leaver for better comfort

Time tested and proven engine

Peep window. Better driving

Bigger rear view mirror

Power steering and air brakes for better control

Passenger comfort and safety

Improved engine cover- low cabin noise

Wide hatrack

High head rest seats with arm rest for better comfort

Large side windows

New tubular structure - safe and robust

Box type chassis frame – high durability

Body features

Pleasing looks

Improved tail lamp and rear fascia

Improved head lamps

Side emergency door

Note: As per our policy of continuous improvement, specifications may change without notice.