

Designed for the need with safety...



School Bus

SCHOOL BUS

Features

- Available in BS-III & BS-IV versions
- Powerful engine-Higher pick up, Higher torque at lower RPM
- Gradeability & Fuel efficient
- Available in BS-III & BS-IV versions
- Powerful engine-Higher pick up, Higher torque at lower RPM

Model	School Bus BS-III	School Bus BS-IV
Engine & Displacement	SLT3 & Numeral , 3455 cc	SLT4 & Numeral , 3455 cc
Type	In line 4-Cylinder Direct Injection	In line 4-Cylinder Common Rail Direct Injection
	Diesel Turbo Charger with Intercooler	
Max Engine Output	75 Kw @3000 rpm	75 Kw @2800 rpm
Max. Torque	270Nm@1750-2000 rpm	296Nm @ 1500 rpm
Clutch	Single plate Diaphragm Type , Dia. 260mm	
Gear Box	Synchromesh Manual 5-Forward and 1-Reverse	
Steering	Mechanical /Power Steering (Optional)	
Brakes	Hydraulic Vacuum assisted/Air Brake (Available only on 50A, 50L and XL Models)	
Suspension	Semi Elliptical Type Multi Leaf Spring	
Variants (Including Driver)	50A	50L
Standard Seats	26	32
Dimensions		
Wheelbase (mm)	3335	3940
Overall Length (mm)	6380	7348
Rear Overhang (mm)	2001	2364
Front Overhang (mm)	1044	1044
Wheels & Tyres	7.50 X 16 - 16PR /8.25 X 16 - 16PR	7.50 X 16 - 16PR /8.25 X 16 - 16PR
No of Tyres	6+1	6+1
Max. Permissible GVW (kg)	6440	6440



Features

- Special hooks for handling water bottles
- Comfortable low height seats
- Storage space for school bags
- Greater safety with warning lights and sound signals for the driver when the entry door is open
- Safety guard rails on window to prevent children from leaning out
- Special governor to limit speed (optional)
- Only vehicle meeting school bus safety requirement and RTO/ARAI norms
- Air conditioned (Optional)

