

Light vehicle for heavy cargo




Supreme

# SUPREME

## Features

- Available in BS-III & BS-IV versions
- Powerful engine, higher pickup, higher torque at lower RPM, Gradeability and fuel efficient
- Heavy duty gearbox and bigger clutch – longer life
- Steering with variable gear ratio – less driver fatigue
- Roof ventilation for better comfort

Model	Supreme BS – III	Supreme BS-IV		
Engine & Displacement	SLT3 & Numeral , 3455 cc	SLT4 & Numeral , 3455 cc		
Type	In line 4-Cylinder Direct Injection	In line 4-Cylinder Common Rail Direct Injection		
Diesel Turbo Charger with Intercooler				
Max.Engine Output	75 Kw @3000 rpm	75 Kw @2800 rpm		
Max. Torque	270Nm@1750-2000 rpm	296Nm @ 1500 rpm		
Clutch	Single plate Diaphragm Type , Dia. 260mm			
Gear Box	Synchromesh Manual 5-Forward and 1-Reverse			
Steering	Mechanical /Power Steering (Optional)			
Brakes	Hydraulic Vaccum assisted			
Suspension	Semi Elliptical Type Multi Leaf Spring			
Wheel & Tyres	7.50" X 16" - 16 PR			
No of Tyres	6 + 1			
Wheelbase (mm)	2815	3335	3940	4760
Min. Turning Circle Diameter (m)	5.5	6.4	7.6	9.4
Front Axle Weight (kg)	2800	2800	2800	2800
Rear Axle Weight (kg)	5200	5200	5200	5200
Kerb Weight (kg)	2750	2800	2900	3000
Max. Permissible GVW (kg)	8000			
Cargo Box Dimensions (LXBXH) (mm)				
Variants				
Cab Halfdeck Loadbody	3740X2080X1030	4260X2080X570	5240X2080X570	6610X2080X570
Cab Semideck Loadbody	3740X2080X1030	4260X2080X1030	5240X2080X1030	Not Available
Cab Highdeck Loadbody	3740X2080X1695	4260X2080X1695	5240X2080X1695	Not Available
Cabin Chasis				



## Features

- Available in BS-III & BS-IV versions
- Powerful engine, higher pickup, higher torque at lower RPM, Gradeability and fuel efficient
- Heavy duty gearbox and bigger clutch – longer life
- Steering with variable gear ratio – less driver fatigue
- Roof ventilation for better comfort
- Ready availability of spares at reasonable price
- Box type chasis with tubular cross members- carry more load, provide better strength and rigidity

